

Computational Intelligence

Winter Term 2013/14

Prof. Dr. Günter Rudolph

Lehrstuhl für Algorithm Engineering (LS 11)

Fakultät für Informatik

TU Dortmund

- ▶ Organization (Lectures / Tutorials)
- ▶ Overview CI
- ▶ Introduction to ANN
 - ◆ McCulloch Pitts Neuron (MCP)
 - ◆ Minsky / Papert Perceptron (MPP)

Who are you?

either

studying “*Automation and Robotics*” (Master of Science)

Module “Optimization”

or

studying “*Informatik*”

- BSc-Modul “Einführung in die Computational Intelligence”

- Hauptdiplom-Wahlvorlesung (SPG 6 & 7)

Who am I ?

Günter Rudolph

Fakultät für Informatik, LS 11

Guenther.Rudolph@tu-dortmund.de

OH-14, R. 232

← best way to contact me

← if you want to see me

office hours:

Tuesday, 10:30–11:30am

and by appointment

Lectures Wednesday 10:15-11:45 SRG1, R. 1.001, weekly

Tutorials either Thursday 16:30-17:30 OH14, R. 1.04, bi-weekly
 or Friday 14:15-15:45 OH14, R. 1.04, bi-weekly

Tutor Dipl.-Inf. Simon Wessing, LS 11

Information

<http://ls11-www.cs.tu-dortmund.de/people/rudolph/teaching/lectures/CI/WS2013-14/lecture.jsp>

Slides see web page

Literature see web page

Knowledge about

- mathematics,
- programming,
- logic

is helpful.

But what if something is unknown to me?

- covered in the lecture
- pointers to literature

... and don't hesitate to ask!

What is CI ?

⇒ umbrella term for computational methods inspired by nature

- artificial neural networks
 - evolutionary algorithms
 - fuzzy systems
 - swarm intelligence
 - artificial immune systems
 - growth processes in trees
 - ...
- } backbone
- } new developments

- term „computational intelligence“ coined by John Bezdek (FL, USA)
- originally intended as a demarcation line
 ⇒ establish border between artificial and computational intelligence
- nowadays: blurring border

our goals:


1. know what CI methods are good for!
2. know when refrain from CI methods!
3. know why they work at all!
4. know how to apply and adjust CI methods to your problem!

Biological Prototype


• Neuron

- Information gathering (D)
- Information processing (C)
- Information propagation (A / S)


human being: 10^{12} neurons
 electricity in mV range
 speed: 120 m / s



Abstraction



Model



McCulloch-Pitts-Neuron 1943:

$$x_i \in \{0, 1\} =: \mathbb{B}$$

$$f: \mathbb{B}^n \rightarrow \mathbb{B}$$

1943: Warren McCulloch / Walter Pitts



- description of neurological networks
→ modell: McCulloch-Pitts-Neuron (MCP)
- basic idea:
 - neuron is either active or inactive
 - skills result from **connecting** neurons
- considered static networks
(i.e. connections had been constructed and not learnt)

McCulloch-Pitts-Neuron

n binary input signals x_1, \dots, x_n

threshold $\theta > 0$

$$f(x_1, \dots, x_n) = \begin{cases} 1 & \text{if } \sum_{i=1}^n x_i \geq \theta \\ 0 & \text{else} \end{cases}$$




McCulloch-Pitts-Neuron

n binary input signals x_1, \dots, x_n

threshold $\theta > 0$

in addition: m binary inhibitory signals y_1, \dots, y_m




$$\tilde{f}(x_1, \dots, x_n; y_1, \dots, y_m) = f(x_1, \dots, x_n) \cdot \prod_{j=1}^m (1 - y_j)$$

- if at least one $y_j = 1$, then output = 0
- otherwise:
 - sum of inputs \geq threshold, then output = 1
 - else output = 0

Assumption:


inputs also available in inverted form, i.e. \exists inverted inputs.



Theorem:

Every logical function $F: \mathbb{B}^n \rightarrow \mathbb{B}$ can be simulated with a two-layered McCulloch/Pitts net.

Example: $F(x) = x_1 x_2 \bar{x}_3 \vee \bar{x}_1 \bar{x}_2 \bar{x}_3 \vee x_1 \bar{x}_4$



Proof: (by construction)


Every boolean function F can be transformed in disjunctive normal form

⇒ 2 layers (AND - OR)

1. Every clause gets a decoding neuron with $\theta = n$
⇒ output = 1 only if clause satisfied (AND gate)
2. All outputs of decoding neurons are inputs of a neuron with $\theta = 1$ (OR gate)

q.e.d.

Generalization: inputs with weights



Theorem:

Weighted and unweighted MCP-nets are equivalent for weights $\in \mathbb{Q}^+$.

Proof:

„ \Rightarrow “ Let $\sum_{i=1}^n \frac{a_i}{b_i} x_i \geq \frac{a_0}{b_0}$ with $a_i, b_i \in \mathbb{N}$

Multiplication with $\prod_{i=0}^n b_i$ yields inequality with coefficients in \mathbb{N}

Duplicate input x_i , such that we get $a_i b_1 b_2 \dots b_{i-1} b_{i+1} \dots b_n$ inputs.

Threshold $\theta = a_0 b_1 \dots b_n$

„ \Leftarrow “

Set all weights to 1.

q.e.d.

Conclusion for MCP nets

- + feed-forward: able to compute any Boolean function
- + recursive: able to simulate DFA
- very similar to conventional logical circuits
- difficult to construct
- no good learning algorithm available

Perceptron (Rosenblatt 1958)

\rightarrow complex model \rightarrow reduced by Minsky & Papert to what is „necessary“

\rightarrow Minsky-Papert perceptron (MPP), 1969 \rightarrow essential difference: $x \in [0,1] \subset \mathbb{R}$

What can a single MPP do?

isolation of x_2 yields:


$$w_1 x_1 + w_2 x_2 \geq \theta \begin{cases} \text{Y} & 1 \\ \text{N} & 0 \end{cases}$$

$$x_2 \geq \frac{\theta}{w_2} - \frac{w_1}{w_2} x_1 \begin{cases} \text{Y} & 1 \\ \text{N} & 0 \end{cases}$$


Example:

$$0,9 x_1 + 0,8 x_2 \geq 0,6$$

$$\Leftrightarrow x_2 \geq \frac{3}{4} - \frac{9}{8} x_1$$



separating line
separates \mathbb{R}^2
in 2 classes




1969: Marvin Minsky / Seymour Papert

- book *Perceptrons* → analysis math. properties of perceptrons
- disillusioning result: **perceptions fail to solve a number of trivial problems!**
 - XOR-Problem
 - Parity-Problem
 - Connectivity-Problem
- „conclusion“: All artificial neurons have this kind of weakness!
 ⇒ research in this field is a scientific dead end!
- consequence: research funding for ANN cut down extremely (~ 15 years)




how to leave the „dead end“:

1. Multilayer Perceptrons:



2. Nonlinear separating functions:



How to obtain weights w_i and threshold θ ?

as yet: by construction

example: NAND-gate

x_1	x_2	NAND
0	0	1
0	1	1
1	0	1
1	1	0

$\Rightarrow 0 \geq \theta$
 $\Rightarrow w_2 \geq \theta$
 $\Rightarrow w_1 \geq \theta$
 $\Rightarrow w_1 + w_2 < \theta$

requires solution of a system of linear inequalities ($\in P$)
 (e.g.: $w_1 = w_2 = -2, \theta = -3$)

now: by „learning“ / training


Perceptron Learning

Assumption: test examples with correct I/O behavior available

Principle:


- (1) choose initial weights in arbitrary manner
- (2) feed in test pattern
- (3) if output of perceptron wrong, then change weights
- (4) goto (2) until correct output for all test patterns

graphically:



→ translation and rotation of separating lines

Example



$$P = \left\{ \begin{pmatrix} 1 \\ 1 \end{pmatrix}, \begin{pmatrix} 1 \\ -1 \end{pmatrix}, \begin{pmatrix} 0 \\ -1 \end{pmatrix} \right\}$$

$$N = \left\{ \begin{pmatrix} -1 \\ -1 \end{pmatrix}, \begin{pmatrix} -1 \\ 1 \end{pmatrix}, \begin{pmatrix} 0 \\ 1 \end{pmatrix} \right\}$$

threshold as a weight: $w = (\theta, w_1, w_2)^t$

$$\begin{matrix} 1 & -\theta \\ x_1 & w_1 \\ x_2 & w_2 \end{matrix} \geq 0$$

$$P = \left\{ \begin{pmatrix} 1 \\ 1 \\ 1 \end{pmatrix}, \begin{pmatrix} 1 \\ 1 \\ -1 \end{pmatrix}, \begin{pmatrix} 1 \\ 0 \\ -1 \end{pmatrix} \right\}$$

$$N = \left\{ \begin{pmatrix} -1 \\ -1 \\ -1 \end{pmatrix}, \begin{pmatrix} -1 \\ -1 \\ 1 \end{pmatrix}, \begin{pmatrix} -1 \\ 0 \\ 1 \end{pmatrix} \right\}$$

suppose initial vector of weights is

$$w^{(0)} = (1, -1, 1)^t$$

Perceptron Learning

P: set of positive examples → output 1
 N: set of negative examples → output 0
 threshold θ integrated in weights

1. choose w_0 at random, $t = 0$
2. choose arbitrary $x \in P \cup N$
3. if $x \in P$ and $w_t^t x > 0$ then goto 2
 if $x \in N$ and $w_t^t x \leq 0$ then goto 2
4. if $x \in P$ and $w_t^t x \leq 0$ then
 $w_{t+1} = w_t + x$; $t++$; goto 2
5. if $x \in N$ and $w_t^t x > 0$ then
 $w_{t+1} = w_t - x$; $t++$; goto 2
6. stop? If I/O correct for all examples!


I/O correct!
 let $w^t x \leq 0$, should be $> 0!$
 $(w+x)^t x = w^t x + x^t x > w^t x$
 let $w^t x > 0$, should be $\leq 0!$
 $(w-x)^t x = w^t x - x^t x < w^t x$

remark: algorithm converges, is finite, worst case: exponential runtime


We know what a single MPP can do.

What can be achieved with many MPPs?

Single MPP ⇒ separates plane in two half planes
 Many MPPs in 2 layers ⇒ can identify convex sets



- ⇐
1. How? ⇒ 2 layers!
 2. Convex?



$\forall a, b \in X:$
 $\lambda a + (1-\lambda) b \in X$
 for $\lambda \in (0,1)$

Single MPP	⇒ separates plane in two half planes
Many MPPs in 2 layers	⇒ can identify convex sets
Many MPPs in 3 layers	⇒ can identify arbitrary sets
Many MPPs in > 3 layers	⇒ not really necessary!

arbitrary sets:

1. partitioning of nonconvex set in several convex sets
2. two-layered subnet for each convex set
3. feed outputs of two-layered subnets in OR gate (third layer)